



### Analogue Multi-Sensor (ACC-EN)

Model ACC-EN is a Multi-Sensor, which is fully compatible with Hochiki's ESP Analogue Addressable Protocol, and incorporates a thermal element and High Performance photoelectric smoke chamber.

The ACC-EN has three modes, which are controlled from the Control Panel, allowing either the optical element or thermal element or both elements to be active in making the fire decision. The sensor polling LEDs can be controlled via the Control Panel (pulsing/non-pulsing). The ACC-EN smoke chamber can easily be removed or replaced for easy maintenance.

## FEATURES

- User selectable modes
- Incorporates Optical & Heat elements
- Removable, High Performance Chamber
- Twin LEDs allow 360 viewing – green when polling, turn red in fire
- Pulsing/non-pulsing controlled from panel\*
- Variable sensitivity
- Electronically Addressed
- LPCB & VdS approved to classes A1 & C
- SIL Level 2 approved variants available
- Available in white or ivory

## SPECIFICATION

Ordering Code	Ivory: ACC-EN White: ACC-EN(WHT)
Operating Voltage	17 – 41 V d.c.
Low Power Mode (typ)	120 uA
Quiescent Current (typ)	400 uA
Alarm Current (controlled by CIE)	9.1 mA (excluding remote indicator)
Transmission Method	Digital Using ESP
Operating Temp Range	-10 °C to + 50 °C
Operating Humidity	95%RH - Non Condensing (at 40 °C)
Storage Temp Range	-30 °C to +60 °C
Storage Humidity	<80% RH at 60 °C
Colour / Case Material	Ivory or White / Polycarbonate
Weight (g)	95
Diameter / Height	100 / 45 mm
Compatible Bases	YBN-R/3, YBO-R/SCI, YBO-BS, YBO-BSB, YBN-R/3(SCI)
Base Fixing Centres	48 ~ 74 mm
Approvals	LPCB & VdS approved to classes A1 & C