



WIRELESS WALL MOUNTED SOUNDER (EUW-WSR-IP-03)

The EUW-WSR-IP-03 Conventional Wall Sounder forms the core of our EN54-3 range. The unit can either be used as a standalone conventional device or as an intelligent unit by the addition of a wired module (100-2050V) or wireless module (EUW-SIM-01). All devices are weatherproof, therefore this combined with the modular approach means the majority of applications can be achieved with very few components. The unit is equipped with 3 levels of volume adjustment and 32 recognised tones which can be set via the control equipment or locally at the sounder.

KEY FEATURES

- Flexible modular design
- 5 year product warranty
- 32 Tone Settings
- 3rd party approval to EN54-3 (Type B)
- Two stage alarm capability
- Weatherproof as standard
- Easy to install
- Microphone self test facility
- Robust & high reliability

TECHNICAL SPECIFICATION

Power supply voltage range	15Vdc – 40Vdc
Activated current load (High Vol.)	5 - 8 mA at 24 Vdc
Acoustic Frequency range	400-2900 Hz
Maximum acoustic Output	100 dB(A) @ 1m
Temperature range (no icing)	-25°C to +70°C
Unit weight (inc Back box)	290g
Max humidity (non condensing)	95% RH
Ingress Protection	Designed to meet IP 65

STANDARDS & APPROVALS

- BS EN 54-3:(Type B) Fire Alarm Device, Sounders

