



Analogue Addressable Manual Call Point with SCI (Orange)

HCP-EO (SCI)

Model HCP-EO(SCI) is a Manual Call Point with integral short-circuit isolator, which is fully compatible with Hochiki's ESP analogue addressable protocol. The unit incorporates a bicoloured LED, which can be selected as pulsing/non-pulsing*1 for communications polling and is continuously lit when the HCP-EO(SCI) is operated – in these two states the LED will show red. The LED will show amber when a short-circuit is present but will switch to red if the unit is activated. The unit operates by pressing the non-frangible (plastic) element and produces a high level ESP interrupt. A built in test function initiated by the control panel ensures the integrity of the device at all times and the device can be tested by insertion of a test key in the underside of the unit. Two terminal blocks are provided for easy connection to the loop wiring.

The unit is addressed using the TCH-B200 Hand Held Programmer for quick and reliable addressing. The unit can be flush mounted as supplied. For surface fixing a suitable back box such as the SR MOUNTING BOX is required (sold separately). An optional glass element is also available.

FEATURES

- Fast response
- Integral short-circuit isolator
- Bi-coloured status LED
- Non-frangible element fitted as standard (conforms to EN54)
- Addressed with TCH-B200 Hand Held Programmer
- Printed "SMOKE VENT" legend
- Surface mounting (includes back box)

SPECIFICATION

Operating Voltage	17 – 41 V d.c.
Low Power Mode	180 μ A (max), 100 μ A (typ)
Quiescent Current	350 μ A (max), 250 μ A (typ)
Alarm Current	10.0 mA (max), 5 mA (typ)
Resistance in positive	100 m Ω when closed (max) 100 k Ω when open (min)
Short-circuit threshold	(typ) 430 Ω
Transmission Method	Digital Communication Using ESP
Operating Temp Range	-10 °C to + 50 °C
Storage Temp Range	-30 °C to + 70 °C
Max Humidity	95% RH- Non Condensing (at 40 °C)
IP Rating	IP24
Colour / Case Material	Orange / Modified Polyphenylene Oxide
Weight	161 g
Dimensions	W89 x H93 x D59.5 (inc back box) mm