



Weatherproof Analogue Addressable Manual Call Point with Short-Circuit Isolator HCP-W(SCI)

Model HCP-W(SCI) is a weatherproof Manual Call Point with integral short-circuit isolator, which is fully compatible with Hochiki's ESP analogue addressable protocol.

The unit incorporates a bi-coloured LED, which can be selected as pulsing/non-pulsing*1 for communications polling and is continuously lit when the HCP-W(SCI) is operated – in these two states the LED will show red. The LED will show amber when a short-circuit is present but will switch to red if the unit is activated. The unit operates by pressing the EN54 compliant non-frangible (plastic) element and produces a high level ESP interrupt.

A built in test function initiated by the control panel ensures the integrity of the device at all times and the device can be tested by insertion of a test key in the underside of the unit. Two terminal blocks are provided for easy connection to the loop wiring.

The unit is addressed using the TCH-B100 Hand Held Programmer for quick and reliable addressing. An optional glass element is also available.

FEATURES

- Fast response
- Integral short-circuit isolator
- Bi-coloured status LED
- Non-frangible element fitted as standard (conforms to EN54)
- Addressed with TCH-B100 Hand Held Programmer
- Surface mounted
- IP67 rated
- LPCB approved to EN54
- SIL Level 2 approved variants available

SPECIFICATION

Ordering Code	HCP-W(SCI)
Operating Voltage	17 – 41 VDC
Low Power Mode	180 uA (max), 100 uA (typ)
Quiescent Current	350 uA (max), 250 uA (typ)
Alarm Current	10.0 mA (max), 5 mA (typ)
Resistance in positive	100 mΩ when closed (max), 100 kΩ when open (min)
Short-Circuit Threshold (typ)	430 Ω
Transmission Method	Digital Communication Using ESP
Operating Temp Range	-10 to +50 C
Storage Temp Range	-30 to +70C
Max Humidity	95%RH- Non Condensing (at 40 C)
Ingress Protection Rating	IP67
Colour / Case Material	Red / Modified Polyphenylene Oxide
Weight	234 g
Dimensions	W98 x H94 x W78 mm