



Eurotech Slave Base Sounder with White Visual Indicator (100-2017V)

The 100-2017V is an aesthetically pleasing low profile 32 tone audio/visual base sounder with combined white visual indicator, suitable for all devices in the Eurotech range of intelligent detectors.

It offers class-leading acoustic and EN54-23 compliant visual performances with extremely low current consumption. When used in conjunction with an associated intelligent detector the unit can be controlled via the cause and effect programming of a compatible control panel utilising the Argus digital protocol.

The unit has integral DIP switches allowing the independent adjustment of both sounder Volume and Tone settings.

KEY FEATURES

- · Compatible with standard remote activation
- Eurotech range compatible base
- Selectable tone/volumes via integral dip switch
- · Easy installation and cabling
- 3rd party approval to EN54-3 (Type A) and EN54-23
- Available in sounder, sounder beacon with white light and sounder beacon with red light options
- Low current consumption
- White ABS FR plastic

TECHNICAL SPECIFICATION

Acoustic output frequency range	440 - 2900 MHz
IP rating	21C
Max acoustic intensity	92.6dBA (tones 1-4 only)
Number of Tones	32
Typical VAD coverage	C 3 - 15 (high power)
Dimensions	129 mm x 44 mm
Weight	210g
Operating Temperature	-10°C to +55°C
Max. humidity (non condensing)	95% RH

STANDARDS & APPROVALS

- BS EN 54-3:2001+A1:2002+A2:2006 Fire alarm devices
- BS EN 54-23:2010 Fire alarm devices Visual Alarm
 Devices



