



## Eurotech EURV-IO-RP Intelligent Input & Output Relay Module (100-2037V)

The Eurotech module range provides an ideal solution to the monitoring and control requirements of most fire detection and alarm systems, ranging from small and simple, to large and complex. By utilising the Eurotech fully digital communication protocol, reliable and fast operation is achieved even when employing the impressive 240 device loop capacity. A choice of mechanical configurations provides easy integration of the units into a variety of field locations. The EURV-IO-RP is mounted on a standard faceplate and can be used with a surface back box or flush mounted and provides the capability to both remotely monitor a single circuit and control a single ancillary circuit using a set of volt-free changeover relay contacts. The input circuit is monitored for fault and an alarm condition. Bi-colour LEDs provide local indication of device status.

## KEY FEATURES

- Employs the highly reliable Eurotech digital protocol
- Integrated short circuit isolators to protect and maintain operation
- Loop powered with very low current consumption
- Monitored input and volt-free output providing changeover relay contacts
- Fast fit plug-in cable connections
- Robust proven design offering operation over a wide temp. range
- Alternate mechanical variants available to satisfy different applications
- LED status indicators for both input and output circuits
- Fits to single gang (deep) back box
- 5 year product warranty

## TECHNICAL SPECIFICATION

Loop voltage range	15Vdc – 40Vdc*
Normal Standby Current	250µA @ 24Vdc
Alarm Current (1-2 red LED)	6-12mA @ 24Vdc
Dimensions	86.5 x 86.5 x 24mm (ex-back box)
Temperature Range (no icing)	-10°C to +55°C
Max output rating	2A @ 30Vdc
Max. humidity (non condensing)	95% RH
Weight	200g
*Min 18Vdc for operation of LED.	

## STANDARDS & APPROVALS

- EN 54-17: Short circuit isolators
- EN 54-18: Input/output devices

