

omnis

by Eurotech



euro**tech**[®]
FIRE SYSTEMS LIMITED

Omnis by Eurotech

Omnis by Eurotech analogue addressable control panels have been designed to be flexible and intuitive for the engineer. The large graphical display provides an easy-to-navigate menu system with simple discernable icons. The panels are fully compatible with Eurotech or Odyssey protocol. Up to 240/254 devices (protocol dependent) can be fitted to each loop and 128 programmable groups are available for powerful cause and effect configuration. The panels also boast a simple auto-learn function and loop diagnostics mode for ease of installation.



Flexible

- Fully compatible with full range of Eurotech and Odyssey protocol addressable devices
- Wireless range of accessories
- Powerful cause and effect configuration with 128 programmable groups
- Up to 240/254 devices per loop
- Access controls via key switch or code entry
- Tailored display to your business. Brand the panel with your logo on the display



Intuitive

- Clear and simple user controls with button icons
- Easy menu navigation with graphical symbols
- Effortless installation with plenty of room inside for cables and panel accessories
- Fast to set up with autolearn function and loop fault diagnostics
- Real time clock
- Date & time stamped events log



Assured

- Approved to EN54-2 & EN54-4
- Manufactured in the UK
- Quality assured with Eurotech unique triple testing process
- Intrinsically Safe Mode (where sparks must be avoided) - compatible with IS barriers
- Internal switch mode PSU ensures stability when loads are applied
- Battery backup; PSU for up to 7Ah batteries (1 -2 loop) or 18Ah batteries (1 - 4 loop)

Dimensions	1-2 loop: 357 W x 310 H x 80 D (mm) 1-4 loop: 463 W x 394 H x 100 D (mm)
Battery capacity	1-2 loop: Up to 7 Ah 24V 1-4 loop: Up to 18 Ah 24V
Auxiliary supply	400mA aux supply output (21-28vdc)
Detection Zones	1-2 loop = 18 1-4 loop = 36
Loop	500mA maximum current per loop
Sounder circuits	2 x 400mA 21-28vdc
Event log	255 events, time & date stamped

Omnis by Eurotech

- One to four loops
- 2 sounder circuits
- Large graphical display
- Approved to EN54-2 & EN54-4
- 255 date & time stamped event logs
- Auto-learn function
- Up to 240/254 devices per loop dependent on protocol
- 128 programmable cause & effect groups
- False alarm management modes
- Delays to outputs
- Program company logo
- Loop fault diagnostics
- Up to 8 panels per network
- Up to 8 repeaters per network
- Shared zones across the network



1-4 Loop



1-2 Loop



enquiry@eurotechfire.com

+44 (0) 203 141 0999

eurotechfire.com

Eurotech Fire Systems Limited

18-20 Stratfield Park
Elettra Avenue
Waterlooville
Hampshire
PO7 7XN
United Kingdom



Fire Industry Association



Assessed to ISO 9001
Cert/LPCB ref. 1213

